Cont. 309,081 DT-6786

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT:

Andreas Almansteotter et al.

SERIAL NO.:

10/820,333

FILED:

April 8, 2004

FOR:

MEASURING DEVICE

EXAMINER:

Nina Yasmin Mafaher

Group: 2855

Mail Stop: Amendment Commissioner of Patents P.O. Box 1450

P.O. Box 1450

Alexandria, VA 22313-1450

INFORMATION DISCLOSURE STATEMENT

Sir:

Pursuant to 37 CFR sections 1.97 and 1.98, applicant respectfully requests that the documents listed on the attached form PTO-1449, be made of record and considered in connection with the examination of this application.

Copies of the listed documents are enclosed. A translation of the foreign language document(s) is not readily available.

10/18/2005 BABRAHA1 00000079 10820333

01 FC:1806

180.00 OP

The documents submitted herewith were cited in a preamble of the above-referenced application and during prosecution of the German application corresponding to the above-referenced application.

DE 693 11 897 T2 discloses a load sensor including a resilient U-shaped wire element 11 anchored at 14, bearing at 15 against an abutment 9, and having its free end 17 co-operating with a scale 19, to register the load applied to the bolt 1, the load causing extension of the bolt 1. The sensor element 11 has the same thermal expansion as the bolt. The anchored end 14 may be fixed directly to the bolt head by being wound into a coil, and the scale is on a disc. The sensor element and the scale may be incorporated into an electrical circuit to produce a visual or audible warning, and to control a tightening tool.

European Patent EP 0 910 50 B1 (corresponds to German Publication DE 697 11 184 T2 cited by the German Patent Office) discloses a method and an apparatus for indicating a load.

German Publication DE 31 48 730 A1 discloses a load measuring device formed of two discs (3,4) and a flexible intermediate member (9) and which is mounted between a nut (5) and a machine part (7). A plurality of different balls (10,11) is embedded in the intermediate member (9). Upon application of a

torque to the nut (5), the balls are displaced within the intermediate member, changing its diameter, which represents a measure of applied force.

German Utility Model DE 78 21 489U1 discloses a load indicating washer in which for a better sidewise release of the inserted material (10), there are provided outlet channels (7) extending up to the outer circumference (8) of the washer.

It is noted that U.S. Patents 3,948,141 and 6,425,718 has been cited by the Examiner.

A check in the amount of \$180 for covering the fee under 37 C.F.P. § 1.17 (p) is enclosed.

Respectfully submitted,

Heexander Stachest

Reg. No. 30,541

Dated: October 12, 2005 Abelman, Frayne & Schwab 666 Third Avenue, 10th Floor New York, NY 10017-5621 212-885-9383

This correspondence is being deposited with the United States Postal Service on October 12, 2005 in an envelope as "Express Mail Post Office to Addressee" Mailing Label Number ER 842 053 350 US addressed to the Honorable Commissioner for Patents, Alexandria, VA 22313-1450.

Hekandy Franchuk

(Rev. 7-80) U.S. Department of Patent and Tradema U.S. Department of Patent and Tradema U.S. Department of Patent and Tradema O PERFORMATION DISCLOSURE CITATION IN AN APPLICATION Use several sheets if necessary)	ark Office	Atty. Docket Cor Cont. 309,08 Applicant And Filing Date	1 (DT-	6786)	Seria 1(
Use several sheets if necessary)		Filing Date	lreas A	lmanstoet	ter et a
The That the state of the state	Γ DOCUME				
	r docume	April			Group
	DOCUME		8, 2004		
U.S. PATENT		ENTS			
*Examiner Document Number Initial	Date	Name	Class	Subclass	Filin If A
AA					1
AB					†
AC					
AD					
AE					_
AF					
AG					
AH					
AI					
AJ					
FOREIGN PATEN	T DOCUMI	ENTS			
Document Number I	Date	Country	Class	Subclass	Transla YES
		many			
	999 Euro				
		many			
OTHER RELATED ART (Including A		nany			
TABLE TAKE (Including A	iuinor, Title, De	ate, Pertinent Pages	s, Etc.)		
Search Report		·			
	·				
AS				*	
		· ·			
AT .					
aminer Date 4	Considered		-		